

V-Gard® H1 Safety Helmet



Technical Specifications



The V-Gard® H1 Safety Helmet and accessories provide exceptional comfort and ease of use in a stylish, low-profile design. The latest innovation in head protection, helping to keep you cool and comfortable until the job is done.



Features

- Fas-Trac® III Pivot ratchet suspension for superior comfort, adjustability and range of motion
- Non-contact foam liner maximizes air flow & breathability for optimal cooling and hygiene
- Field replaceable 4-point chinstraps with multiple adjustment points for customized fit and comfort
- Convenient rescue whistle integrated into the chin strap buckle
- Premium sweatband with sweat-wicking fabric, breathable foam and Velcro® attachment for easy field replacement
- Patent pending “push-button” accessory attachment rail and universal clips for head lamps enables quick installation and removal, with no need for an additional carrier
- Standard reflective stickers

Markets

- Utilities
- Industrial Subcontractors
- Oil, Gas & Petrochemical
- Military
- General Industry
- Rescue services
- Construction

Applications

- Working-at-heights
- General Industry
- Confined Space
- Construction
- Rescue
- Forestry works

Customization

- Multiple printing services: one-color logo to digital photos, including individually personalized logos
- Up to three logo locations: Front, Back Left, Back Right

Care & Maintenance

- Clean helmet assembly regularly with mild soap (no detergents) and warm water
- Do not throw, drop, use as support or abuse helmet to ensure proper working condition
- Store helmet in clean, dry environment, 5-35°C (41-95°F)

Service Life Guidelines


- V-Gard Helmets are made with high-quality, wear-resistant materials
- Inspect the helmet before and after each use and replace any part(s) as required
- Always replace the helmet after it has withstood an impact or penetration. MSA recommends:
 - replacing the suspension after no more than 12 months of use
 - replacing the chinstrap after no more than 12 months of use
 - replacing the shell after no more than five (5) years of use
- Storage life is 2 years from date of manufacture when stored as directed
- Warranty: 1 year from date of purchase (free from manufacturer’s defects)
- Please consult user instructions for additional details

Technical Assistance/Additional Information

For more information about V-Gard Helmets and other MSA products, please contact your local MSA customer service or visit MSAsafety.com.



V-Gard H1 Safety Helmet

Technical Specifications			
	Novent	Trivent	Bivent
STANDARDS COMPLIANCE	EN 397:2012+A1:2012 EN 50365:2002-05 ANSI/ISEA Z89.1-2014 CSA Z94.1-2015	EN 12492:2012-04 ANSI/ISEA Z89.1-2014	EN 397:2012+A1:2012 ANSI/ISEA Z89.1-2014 CSA Z94.1-2015
OPTIONAL REQUIREMENTS (EN)	-30°C, 440 V AC		-30°C
OPTIONAL REQUIREMENTS (ANSI)	LT (Low Temp) HV (<i>Hi-Viz, as indicated</i>)	LT (Low Temp) HT (High Temp) HV (<i>Hi-Viz, as indicated</i>)	LT (Low Temp) HV (<i>Hi-Viz, as indicated</i>)
ANSI Z89.1 & CSA Z94.1 CLASSIFICATION	Type 1, Class E	Type 1, Class C	Type 1, Class C
3RD PARTY CERTIFICATIONS	SEI and BG BAU	SEI and BG BAU	SEI and BG BAU
STYLE	Non-vented	Vented	Vented
4-POINT CHIN STRAP	EN 397 Compliant	EN 12492 Compliant	EN 397 Compliant
PRODUCT SIZE	Standard Head Size 6 ½ - 8 (52-64 cm head circumference)	Standard Head Size 6 ½ - 8 (52-64 cm head circumference)	Standard Head Size 6 ½ - 8 (52-64 cm head circumference)
COLORS	Nine (9) Pearlized matte finish.	Nine (9) Pearlized matte finish.	Nine (9) Pearlized matte finish.
SHELL	Virgin high-density polyethylene (HDPE) with UV inhibitor	Virgin high-density polyethylene (HDPE) with UV inhibitor	Virgin high-density polyethylene (HDPE) with UV inhibitor
INTERIOR FOAM	Polystyrene	Polystyrene	Polystyrene
SUSPENSION	Nylon and polypropylene	Nylon and polypropylene	Nylon and polypropylene
CHINSTRAP	Polyester and acetal	Polyester and acetal	Polyester and acetal
SWEATBAND	Polyester	Polyester	Polyester
ACCESSORIES	Eye/Face Protection: Clear & Tinted Spectacles, Clear Full Face Visor, Mesh Visor Type 14 Slotted Hearing Protection Neck Capes, Cooling Pads & Winter Liners		
			
PRODUCT DIMENSIONS	10.3" x 8.4" x 6.5" (25.4 cm x 20.3 cm x 15.3 cm)	10.3" x 8.4" x 6.5" (25.4 cm x 20.3 cm x 15.3 cm)	10.3" x 8.4" x 6.5" (25.4 cm x 20.3 cm x 15.3 cm)
PRODUCT WEIGHT	1,10 lbs (500g)	1,14 lbs (515g)	1,09 lbs (495 g)
MIN ORDER QUANTITIES (MOQ)	Stocked Color, No Logo: 1 Stocked Color with Logo(s): 10	Stocked Color, No Logo: 1 Stocked Color with Logo(s): 10	Stocked Color, No Logo: 1 Stocked Color with Logo(s): 10
SHIPPING CARTON DIMENSION	11.0" x 9.5" x 8.3" (28.0 cm x 22.9 cm x 20.3 cm) <i>(individually packaged)</i>	11.0" x 9.5" x 8.3" (28.0 cm x 22.9 cm x 20.3 cm) <i>(individually packaged)</i>	11.0" x 9.5" x 8.3" (28.0 cm x 22.9 cm x 20.3 cm) <i>(individually packaged)</i>
SHIPPING CARTON WEIGHT (SINGLE)	2.64 lbs (0.9 kg)	2.67 lbs (0.9 kg)	2.64 lbs (0.9 kg)

Note: This Bulletin contains only a general description of the products shown. While product uses and performance capabilities are generally described, the products shall not, under any circumstances, be used by untrained or unqualified individuals. The products shall not be used until the product instructions/user manual, which contains detailed information concerning the proper use and care of the products, including any warnings or cautions, have been thoroughly read and understood. Specifications are subject to change without prior notice.

MSA operates in over 40 countries worldwide. To find an MSA office near you, please visit [MSAafety.com/offices](https://www.MSAafety.com/offices).